# **ENCLOSURE RECOMMENDATIONS**

### **Optimum Sealed Volume**


Internal volume: .4ft3/11.32L

Enclosure "Q": .9 -3dB response: 65Hz

Maximum power handling: 300 watts

Dimensions already include woofer displacement compensation.





9.5'

11"

Cu. feet/liters	"Q"	-3dB	Max Power Handling (PE)
small sealed volume: .23/6.51	1.1	74Hz	300 watts
large sealed volume: .72/20.38	.7	62Hz	300 watts

### **Optimum Vented Volume**

Internal volume: 1.2ft3/33.98L Tuning frequency: 34Hz Port (D x L): 3" X 11"

-3dB response: 39Hz

Maximum power handling: 300 watts


Dimensions already include woofer displacement compensation, but DO NOT include port displacement.

Cu. feet/liters

small vented volume: .9/25.48

large vented volume: 1.5/42.47





14.25


14.5"

Port	-3dB	Max Power Handling (PE)
3" X 12"	45Hz	300 watts
3" x 12.5"	35Hz	300 watts

### **Optimum Bandpass Volume**

Please contact Crossfire
Tech Support for bandpass
enclosure
recommendations





Note: Dimensions for recommended enclosure are with consideration of using .75" (19mm) MDF board. Be sure to add .050ft3/1.41L for driver displacement as well as the volume of the port to all enclosures, except for the optimum recommendation as those already include woofer displacement but DO NOT include port displacement.

## **Crossfire Tech Support Contact Information**

Tune to

38Hz 29Hz

Phone: (562) 906-0800 E-mail: Tech@crossfirecaraudio.com Techsp@crossfirecaraudio.com (asistencia en español)

## DAMPING MATERIAL

The most common damping materials used are Dacron and Polyfill. Reclaimed fiber underlay has been discovered to be an excellent substitute especially when glued directly to the walls of the enclosure. Fiberglass may be used, but please limit usage to sealed enclosures only. When used in vented/bandpass enclosures, fiberglass fibers escaping through the port may be hazardous to your health.

SEALED ENCLOSURE VENTED ENCLOSURE BANDPASS (sealed chamber) BANDPASS (vented chamber) DACRON/POLYFILL loosely fill the enclosure line 3-5 walls line 3 walls line 1 wall (optional) UNDERLAY line 5 walls line 1-3 wall line 1-3 wall line 1 wall (optional) FIBERGLASS line 5 walls Please limit the use of fiberglass to sealed enclosures only

## SPECIFICATIONS

Model	DB310
Driver description	10" Subwoofer, Single Voice Coil
Mounting depth, in/mm	4.875/124
Cutout diameter, in/mm	9.25/235
Woofer Outer Diameter, in/mm	10.6/268
Woofer Displacement, ft3/ltr	.050/1.42
Impedance	4 ohm
Nominal power handling (RMS)	175 watts
Maximum power handling (PE)	300 watts
Dynamic power handling	550 watts
Voice coil – size	2", 4 layer
Magnet weight	45 oz.
Frequency response	22 to 500Hz
Resonance frequency (fs)	28.87Hz
Qts	.39
Qms	7.18
Qes	.41
VAS, ft./liter	1.67/47.38
X-max, in./mm	.312/8
Efficiency (2.83V/1M)	86dB

# **POWER RATINGS**

Rating the power handling of subwoofers is not a difficult task. However, understanding power ratings is often confusing. Many times the Maximum Power Ratings are viewed as the RMS power handling of the driver, when in actuality Maximum is generally the break point of the driver. This has lead Crossfire to come up with a system to rating the power necessary to drive our subwoofers. Please read the following cautiously before choosing your amplifier or with consideration of the power you may already have.

#### Nominal power handling

Nominal power handling is the power rating given by Crossfire at which the subwoofer will experience minimal mechanical degradation over time when using a recommended enclosure. In other words, this is the recommended power to be used per woofer to assure long life.

#### Maximum power handling (PE)

Maximum power handling is the power rating given by Crossfire at which the subwoofer could experience a high amount of mechanical degradation that may lead to possible failure over time when using a recommended enclosure. In other words, do not exceed this power level for extended periods of time.

#### Dynamic power handling

Dynamic power handling is the power rating given by Crossfire for peak transients and short bursts. Continuous playing at or above this level will cause mechanical failure and/or thermal failure. In other words, this power level should never be attained with the exceptions of approved SPL competition vehicles. This could possibly void your warranty.